



**219 SERIES CURRENT SENSE INDUCTORS 40Hz TO 20kHz**

**Features**

- Designed to meet large Secondary Saturation Voltage
- Accurate Turns Ratio
- High Dielectric Strength Capacity 2500VRMS
- Fully molded construction with center thru hole for Primary Load
- Tinned Leads with Leaded Solder is Available (note 2)



**ELECTRICAL SPECIFICATIONS AT 25°C**

Part Number	I Peak AMP	Volt Per AMP	Rated Terminating Ohms (Nominal)	R.C.F. at		Outline Dimensions					
				100% IP	10% IP	L	W	H	ID	X	Y
PT21901	3.5	0.20	200	100.0	102.80	0.625	0.625	0.625	0.188	0.5	0.40
PT21903	5.0	0.20	200	100.0	101.37	0.625	0.625	0.625	0.188	0.5	0.40
PT21905	10.0	0.10	200	100.0	100.87	0.625	0.625	0.625	0.188	0.5	0.40
PT21906	15.0	0.05	100	100.0	100.40	0.625	0.625	0.625	0.188	0.5	0.40
PT21907	20.0	0.025	50	100.0	100.30	0.625	0.625	0.625	0.188	0.5	0.40
PT21925	25.0	0.10	100	100.0	100.90	1.375	0.625	1.375	0.500	1.0	0.50
PT21926	30.0	0.10	100	100.0	100.80	1.375	0.625	1.375	0.500	1.0	0.50

**Notes:**

1. Please consult factory for additional or custom requirements.
2. For non-RoHS parts, replace PT prefix with 42- (e.g. PT12910 becomes 42-12910).
3. Terminal finish is compliant to RoHS requirements

